

FloorEverDri™

UNIVERSAL PRIMER MOISTURE AND ALKALINITY PROTECTION

FEATURES AND BENEFITS

- Exceeds ASTM F3010-13 requirements for vapor reduction when tested in accordance with ASTM E96 (< .1 O perm)
- Unaffected by pH 14 (ASTM D1308)
- BPA free, water-based and non-toxic
- Not a reactive silicate

WHERE TO USE

- Lightweight or structural concrete
- On, below or above grade slabs
- Beneath moisture and alkaline sensitive floor covering installations on sound, clean, absorbent concrete

LIMITATIONS

- Do not allow product to freeze
- Do Not use on floors containing Asbestos
- Ambient and concrete surface temperatures must be at least 40°F Optimum installation temperatures are between 45°F and 100°F
- Do not thin product

MIXING AND PRODUCT APPLICATION

- Concrete must be clean, absorbent and free of bond-breakers, sealers or contaminants preventing proper adhesion of product prior to and during application.
- Agitate by hand to ensure product has a uniform consistency prior to application.

DO NOT USE DRILL OR HIGH SPEED MIXING METHOD

- Apply uniformly in a singular direction, back rolling immediately utilizing a 3/8" nap roller.
- Do not allow to puddle
- Always apply according to manufacturers application specifications.

CLEANUP

Clean tools and equipment with soap and water immediately after use.

PACKAGING AND HANDLING

Packaging	5 us gallon pail (18.9 L)
Shelf Life	12 months unopened
Consistency	Liquid
Color	Milky white, dries clear
Storage Range	Between 65°F - 90°F

Refer to product SOS for specific data related to health, safety and handling.

CSI DIVISION CLASSIFICATIONS

Concrete Curing	03 3900
Vapor Control for Flooring	09 6105

PRODUCT PERFORMANCE PROPERTIES

Solids Content	25%
VOC's	Og/l
Moisture Loss	<0.40 kg/m ²
Net Permeance	<.10 perms
Coverage	250-300sf/gal
Dry Time (73°/50%RH)	60 minutes
Alkalinity Resistance	Pass (ASTM D1 308)
Concrete Bond Strength	>250psi
Mastic Adhesion	>70psi

For Professional Use Only

FloorEverDri™ is intended for use by trained professionals only.

WARRANTY

Uniseal Solutions, Inc. warrants the product to be free of manufacturing defects and to conform to published product performance properties.

The foregoing warranty shall be exclusive and in lieu of any other warranties, expressed or implied, including but not limited to warranties of merchantability and fitness for a particular purpose. Before using, user shall determine the suitability of the product for its' intended use and assume all risks and associated liability whatsoever in connection with.

For project specific warranties contact UniSeal Solutions, Inc.

SECTION 1: Trade name: FloorEverDri™

Application of the substance / the mixture: Sealing
Manufacturer: Uniseal Solutions, Inc. 66 Murray Pl., York, PA 17403
Main: (717) 852-7342 Emergency: Chem Tel Inc. (800) 255-3924, +1 (813) 248-0585

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
Classification according to Regulation (EC) No 1272/2008
The product is not classified as hazardous according to GHS regulations.
The product is not classified as hazardous according to OSHA GHS regulations within the United States.
The product is not classified as hazardous according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the Globally Harmonised System (GHS).
The product is not classified as hazardous according to the CLP regulation.
The product is not classified as hazardous according to OSHA GHS regulations within the United States.
Hazard pictograms Not Regulated
Signal word Not Regulated
Hazard-determining components of labelling: None.
Hazard statements Not Regulated

SECTION 4: First aid measures

- 4.1 Description of first aid measures
Alter inhalation: Supply fresh air; consult doctor in case of complaints.
Alter skin contact: Clean with water and soap.
If skin irritation continues, consult a doctor.
Alter eye contact: Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Alter swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed
- Nausea
 - Cramp
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
Smaller quantities can be disposed of with household waste.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
Uncleaned packaging:
Disposal must be made according to official regulations.


UniSeal
SOLUTIONS
Intrinsic material technology™